# Nextorage

### Datasheet 2.5 Inch SATA SSD A2 Series 3D TLC Model

- Supports SATA 6Gbps
- Highly reliable PLP with our in-house firmware
- High Performance with DRAM mounts
- 3D TLC NAND implemented
- RAID ECC equipped
- Aluminum Case enclosure
- Supports S.M.A.R.T. and TRIM Command



Nextorage A2 Series is a high performing SATA SSD with extremely reliable PLP (Power Loss Protection) technology. Its durability is accomplishable because of our in-house firmware implementation. A2 Series is suitable for embedded PCs, edge computing, security cameras, boot drive such as video editing devices, and as a reliable data storage.

### Support Available for Industrial Grade Embedded Devices

Fixed BOM for major components	Failure Analysis Report	Technical Support	
--------------------------------------	-------------------------------	----------------------	--

# Nextorage

#### **Product Specification**

Model Name	NA22HE0000C120G	NA22HE0000C240G	NA22HE0000C480G
Capacity	120GB	240GB	480GB
Number of sectors	234,441,648	468,862,128	937,703,088
Interface	Compatible with SATA 1.5Gbps, 3Gbps, and 6Gbps		
Flash Type	3D TLC		
Seq. R/W*1	430/170 MB/s	560/540 MB/s	560/540 MB/s
Rnd. R/W*2	46 / 18 KIPOS	79 / 49 KIPOS	76 / 53 KIPOS
Average Power Consumption (Max)	1800mW	1950mW	2550mW
Operation Temp.	0℃ to 70℃		
Storage Temp.	-40℃ to 85℃		
Dimensions	100mm x 70mm x 7mm (L x W x H)		
SPQ*3	100pcs		

Model Name	NA22HE0000CA01T	NA22HE0000CA02T	
Capacity	960GB	1920GB	
Number of sectors	1,875,385,008	3,750,748,848	
Interface	Compatible with SATA 1.5Gbps, 3Gbps, and 6Gbps		
Flash Type	3D TLC		
Seq. R/W*1	560/540 MB/s	560/540 MB/s	
Rnd. R/W*2	84K / 78KIPOS	87K / 90KIPOS	
Average Power Consumption (Max)	2800mW	2800mW	
Operation Temp.	Compatible with SATA 1.5Gbps, 3Gbps, and 6Gbps		
Storage Temp.	-40℃ to 85℃		
Dimensions	100mm x 70mm x 7mm (L x W x H)		
SPQ*3	100pcs		

\*1 The performance was measured using CrystalDiskMark v6.0.2x64 with SATA 6Gbps host.

 $^{\ast}2$  Measured under IOmeter Range 1GB, data size 4KB, QD=32, and Thread=8

Performance may differ depending on the flash configuration and platform.

\*3 Standard Packing Quantity = Unit of Purchase

#### Nextorage Corporation

Contact

Kawasaki-eki-mae Tower Riverk 9F, Ekimaehoncho 12-1, Kawasaki-ku, Kawasaki City, Kanagawa 210-0007, Japan

gp-b2b-inquiry@nextorage.jp